

CRD15

Cradle for H15



+ Specifications

Communication

- USB: Ver. 1.1, client, VCP, USB-A connector

Power

- Voltage requirement: 6V
- Battery charging time: Ca. 3 hours

Physical

- Dimensions (w x h x d):
72 x 75 x 115 mm / 2.83 x 2.95 x 4.53 in
- Weight body: Ca. 180 g / 6.3 oz
- Case: ABS, Black

Regulatory & Safety

- Product compliance: CE incl. LVD, FCC, cUL, RoHS

Enclosed items

- USB cable
- Power supply 100-240V/0.5A, 50/60 Hz, 6V/2A

Copyright Opticon. All rights reserved. This information is subject to change without prior notice. For availability, contact your local representative.

- **The Netherlands:** Hoofddorp
- **France:** Issy Les Moulineaux
- **Germany:** Dietzenbach
- **Italy:** Castel Maggiore (BO)
- **Spain:** Valencia
- **Sweden:** Järfälla
- **United Kingdom:** Luton, Bedfordshire
- **U.S.A.:** Renton, WA
- **Japan:** Warabi City

- **Taiwan:** Taipei
- **P.R.China:** Shanghai
- **Australia:** Kariong
- **Brazil:** São Paulo

Opticon Mobility Solutions
2220 Lind Avenue SW
Suite 100
Renton, WA 98057
Toll Free: (800) 636-0090
Local: (425) 651-2120
Fax: (425) 454-0865
Email: sales@opticonusa.com



www.opticonmobility.com