

# IRU8000

## Cradle for PHL8000 series



### + Specifications

#### Communication

- RS232: Full function support
- USB: Ver. 1.1, USB-A connector

#### Power

- Voltage requirement: 5V
- Battery charging time: Standard battery ca. 3 hours, High-capacity battery ca. 6 hours

#### Durability

- Temperature in operation: -10 to 50 °C / 14 to 122 °F
- Temperature in storage: -20 to 60 °C / -4 to 140 °F
- Drop test: 0.75 m / 2.5 ft drop onto concrete surface

#### Physical

- Dimensions (w x h x d):  
134 x 58 x 141 mm / 5.28 x 2.28 x 5.55 in
- Weight body: 475 g / 1 lbs 0.8 oz
- Case: ABS, Black

#### Regulatory & Safety

- Product compliance: CE incl. LVD, FCC, cUL, RoHS

#### Enclosed items

- USB cable

#### Sold separately

- RS232 cable
- Power supply 100-240V/0.6A, 50/60 Hz, 5V/2.6A

Copyright Opticon. All rights reserved. This information is subject to change without prior notice. For availability, contact your local representative.

- **The Netherlands:** Hoofddorp
- **France:** Issy Les Moulineaux
- **Germany:** Dietzenbach
- **Italy:** Castel Maggiore (BO)
- **Spain:** Valencia
- **Sweden:** Järfälla
- **United Kingdom:** Luton, Bedfordshire
- **U.S.A.:** Renton, WA
- **Japan:** Warabi City

- **Taiwan:** Taipei
- **P.R.China:** Shanghai
- **Australia:** Kariiong
- **Brazil:** São Paulo

Opticon Mobility Solutions  
2220 Lind Avenue SW  
Suite 100  
Renton, WA 98057  
Toll Free: (800) 636-0090  
Local: (425) 651-2120  
Fax: (425) 454-0865  
Email: sales@opticonusa.com



[www.opticonmobility.com](http://www.opticonmobility.com)